

Casing pipes as per Specification API 5CT/5B

Length	Range 2	8,530	9,750	meters	30 feet	
	Range 3	11,580	13,720	meters	40 feet	
Outside diameter		Wall thickness		Short thread Casing	Long thread Casing	Buttress thread Casing
mm	inch	mm	inch			
114,30	4,50	5,21	0,205	H40 J55 K55	X	X
114,30	4,50	5,69	0,224	J55 K55	X	J55 K55
114,30	4,50	6,35	0,250	J55 K55	J55 K55 N80 P110	J55 K55 N80 P110
114,30	4,50	7,37	0,290	X	N80 P110	N80 P110
114,30	4,50	8,56	0,337	X	P110	P110
127,00	5,00	5,59	0,220	J55 K55	X	X
127,00	5,00	6,43	0,253	J55 K55	J55 K55	J55 K55
127,00	5,00	7,52	0,296	J55 K55	J55 K55 N80 P110	J55 K55 N80 P110
127,00	5,00	9,19	0,362	X	N80 P110	N80 P110
127,00	5,00	11,10	0,437	X	N80 P110	N80 P110
127,00	5,00	12,14	0,478	X	N80 P110	N80 P110
127,00	5,00	12,70	0,500	X	N80 P110	N80 P110
139,70	5,50	6,20	0,244	H40 J55 K55	X	X
139,70	5,50	6,98	0,275	J55 K55	J55 K55	J55 K55
139,70	5,50	7,72	0,304	J55 K55	J55 K55 N80 P110	J55 K55 N80 P110
139,70	5,50	9,17	0,361	X	N80 P110	N80 P110
139,70	5,50	10,54	0,415	X	N80 P110	N80 P110
168,28	6,63	7,32	0,288	H40 J55 K55	J55 K55	J55 K55
168,28	6,63	8,94	0,352	J55 K55	J55 K55 N80 P110	J55 K55 N80 P110
168,28	6,63	10,59	0,417	X	N80 P110	N80 P110
168,28	6,63	12,06	0,475	X	N80 P110	N80 P110
177,80	7,00	5,87	0,231	H40	X	X
177,80	7,00	6,91	0,272	H40 J55 K55	X	X
177,80	7,00	8,05	0,317	J55 K55	J55 K55 N80	J55 K55 N80
177,80	7,00	9,19	0,362	J55 K55	J55 K55 N80 P110	J55 K55 N80 P110
177,80	7,00	10,36	0,408	X	N80 P110	N80 P110
177,80	7,00	11,51	0,453	X	N80 P110	N80 P110
177,80	7,00	12,65	0,498	X	N80 P110	N80 P110

177,80	7,00	13,72	0,540	X	N80 P110	N80 P110
193,68	7,63	7,62	0,300	H40	X	X
193,68	7,63	8,33	0,328	J55 K55	J55 K55 N80	J55 K55 N80
193,68	7,63	9,52	0,375	X	N80 P110	N80 P110
193,68	7,63	10,92	0,430	X	N80 P110	N80 P110
193,68	7,63	12,70	0,500	X	N80 P110	N80 P110
193,68	7,63	14,27	0,562	X	N80 P110	N80 P110
219,08	8,63	6,71	0,264	J55 K55	X	X
219,08	8,63	7,72	0,304	H40	X	X
219,08	8,63	8,94	0,352	H40 J55 K55	J55 K55	J55 K55
219,08	8,63	10,16	0,400	J55 K55	J55 K55 N80	J55 K55 N80
219,08	8,63	11,43	0,450	X	N80 P110	N80 P110
219,08	8,63	12,70	0,500	X	N80 P110	N80 P110
219,08	8,63	14,15	0,557	X	N80 P110	N80 P110
244,48	9,63	7,92	0,312	H40	X	X
244,48	9,63	8,94	0,352	H40 J55 K55	J55 K55	J55 K55
244,48	9,63	10,03	0,395	J55 K55	J55 K55 N80	J55 K55 N80
244,48	9,63	11,05	0,435	X	N80 P110	N80 P110
244,48	9,63	11,99	0,472	X	N80 P110	N80 P110
244,48	9,63	13,84	0,545	X	N80 P110	N80 P110
244,48	9,63	15,11	0,595	X	N80 P110	N80 P110
273,05	10,75	7,09	0,279	H40	X	X
273,05	10,75	8,89	0,350	H40 J55 K55	X	J55 K55
273,05	10,75	10,16	0,400	J55 K55	X	J55 K55
273,05	10,75	11,43	0,450	J55 K55 N80 P110	X	J55 K55 N80 P110
273,05	10,75	12,57	0,495	N80 P110	X	N80 P110
273,05	10,75	13,84	0,545	P110	X	P110
273,05	10,75	15,11	0,595	P110	X	P110
298,45	11,75	8,46	0,333	H40	X	X
298,45	11,75	9,53	0,375	J55 K55	X	J55 K55
298,45	11,75	11,05	0,435	J55 K55	X	J55 K55
298,45	11,75	12,42	0,489	J55 K55 N80 P110	X	J55 K55 N80 P110
298,45	11,75	13,56	0,534	N80 P110	X	N80 P110
298,45	11,75	14,78	0,582	N80 P110	X	N80 P110
339,73	13,38	8,38	0,330	H40	X	X
339,73	13,38	9,65	0,380	J55 K55	X	J55 K55
339,73	13,38	10,92	0,430	J55 K55	X	J55 K55

339,73	13,38	12,19	0,480	J55 K55 N80 P110	X	J55 K55 N80 P110
339,73	13,38	13,06	0,514	N80 P110	X	N80 P110
406,40	16,00	9,53	0,375	H40	X	X
406,40	16,00	11,13	0,438	J55 K55	X	J55 K55
406,40	16,00	12,57	0,495	J55 K55	X	J55 K55
473,08	18,63	11,05	0,435	H40 J55 K55	X	X
508,00	20,00	11,13	0,438	H40 J55 K55	H40 J55 K55	X
508,00	20,00	12,70	0,500	J55 K55	J55 K55	J55 K55
508,00	20,00	16,13	0,635	J55 K55	J55 K55	J55 K55