

Steel drill pipes 5D

Length	Range 1	5,490	6,710	meters	22 feet	
	Range 2	8,230	9,140	meters	30 feet	
	Range 3	11,580	13,720	meters	40 feet	
Outside diameter		Wall thickness		External upset	Internal upset	Internal External upset
mm	inch	mm	inch	Connection type		
60,30	2 3/8	7,11	0,280	NC26(2 1/8 IF)	X	X
E75, X95, G105, S135*						
73,02	2 7/8	9,19	0,362	NC31(2 7/8 IF)	X	X
E75, X95, G105, S135						
88,90	3 1/2	9,35	0,368	NC38(3 1/2 IF)	X	X
E75, X95, G105, S135						
88,90	3 1/2	11,40	0,449			
E75, X95, G105				NC38(3 1/2 IF)	X	X
S135				NC40(4 FH)	X	X
101,60	4	8,38	0,330	NC46(4 IF)	NC40(4 FH)	X
E75, X95, G105, S135						
114,30	4 1/2	8,56	0,337	NC50(4 1/2 IF)	X	NC46(4 IF)
E75, X95, G105, S135						
114,30	4 1/2	10,92	0,430	NC50(4 1/2 IF)	X	NC46(4 IF)
E75, X95, G105, S135						
127,00	5	9,19	0,362	X	X	NC50(4 1/2 IF) or 5 1/2 FH
E75, X95, G105, S135						
127,00	5	12,70	0,500	X	X	5 1/2 FH
E75, X95, G105, S135						

139,70	5 ½	9,17	0,361	X	X	5 ½ FH
E75, X95, G105, S135						
139,70	5 ½	10,54	0,415	X	X	5 ½ FH
E75, X95, G105, S135						