

Tubing pipes as per Specification API 5CT/5B

Length	Range 1	6,100	7,320	meters	22 feet
	Range 2	8,530	9,750	meters	30 feet
	Range 3	11,580	12,800	meters	40 feet
Outside diameter		Wall thickness		External upset	None upset
mm	inch	mm	inch	Steel grade	
60,32	2 3/8	4,24	0,167	X	H40, J55, N80
60,32	2 3/8	4,83	0,190	H40, J55, N80, P110	H40, J55, N80, P110
60,32	2 3/8	6,45	0,254	N80, P110	N80, P110
73,02	2 7/8	5,51	0,217	H40, J55, N80, P110	H40, J55, N80, P110
73,02	2 7/8	7,01	0,276	N80, P110	N80, P110
73,02	2 7/8	7,82	0,308	N80, P110	N80, P110
88,90	3 1/2	5,49	0,216	X	H40, J55, N80
88,90	3 1/2	6,45	0,254	H40, J55, N80, P110	H40, J55, N80, P110
88,90	3 1/2	7,34	0,289	X	H40, J55, N80
88,90	3 1/2	9,52	0,375	N80, P110	N80, P110
101,60	4	5,74	0,226	X	H40, J55, N80
101,60	4	6,65	0,262	H40, J55, N80	X
114,30	4 1/2	6,88	0,271	H40, J55, N80	H40, J55, N80