



SPECIFICATIONS			
Bottom Thread	4-1/2" O.D. 8rd*	5-1/2" O.D. 8rd*	7" O.D. 8rd*
Bottom Connection	Male, Female, SOW	Male, Female, SOW	Male, Female, SOW
Working Pressure	2000 or 3000 PSI	2000 or 3000 PSI	2000 or 3000 PSI
Test Pressure	4000 & 6000 PSI	4000 & 6000 PSI	4000 & 6000 PSI
Max. Slip Load (2:1 SF)	85,000 lbs.	85,000 lbs.	85,000 lbs.
Cap Thread	8-5/8" API Modified**	8-5/8" API Modified**	8-5/8" API Modified**
Cap Material	Ductile Iron	Ductile Iron	Ductile Iron
Inner String & Stripper Rubber	2-1/16", 2-3/8" & 2-7/8"	2-1/16", 2-3/8", 2-7/8", 3-1/2" & 4"	2-1/16", 2-3/8", 2-7/8", 3-1/2", 4" & 4-1/2"
Suspension	Slip or Mandrel	Slip or Mandrel	Slip or Mandrel
Side Outlet	2" LP	2" LP	2" LP
Minimum Bore	4.090"	5.012"	6.456"
Body Material	Carbon Steel	Carbon Steel	Carbon Steel
Height	13-7/8" (SR 19-5/8")	13-7/8" (SR 19-5/8")	13-7/8" (SR 19-5/8")
Weight	132 lbs. (SR 202 lbs.)	132 lbs. (SR 202 lbs.)	132 lbs. (SR 202 lbs.)

\* Other thread styles available upon request of special order

\*\* Caution: WSI recommends using only API modified threaded WSI drilling flanges