



**MODEL "S"**

<b>SPECIFICATIONS</b>		
<b>Bottom Thread</b>	4-1/2" O.D. 8rd	5-1/2" O.D. 8rd
<b>Bottom Connection</b>	Male, Female	Male
<b>Working Pressure</b>	1500 PSI	1500 PSI
<b>Test Pressure</b>	3000 PSI	3000 PSI
<b>Max. Slip Load (2:1 SF)</b>	45,000 lbs.	45,000 lbs.
<b>Cap Thread</b>	5-1/2" O.D. 8rd	5-1/2" O.D. 8rd
<b>Cap Material</b>	Ductile Iron	Ductile Iron
<b>Inner String &amp; Stripper Rubbers</b>	1-1/2", 2-3/8" & 2-7/8"	1-1/2", 2-3/8" & 2-7/8"
<b>Suspension</b>	Slip or Mandrel	Slip or Mandrel
<b>Side Outlet</b>	2" LP	2" LP
<b>Minimum Bore</b>	4.090"	4.090"
<b>Body Material</b>	Ductile Iron	Ductile Iron
<b>Height</b>	9-5/8" (SS 14-1/4")	11-1/2" (SS 16-1/8")
<b>Weight</b>	48 lbs. (SS 70 lbs.)	48 lbs. (SS 70 lbs.)

**NOTE:** Spider cap also available

**IMPORTANT NOTE:** Midget Model "S" available upon request