



HYBRID MODEL "R" 7"

HYBRID MODEL "R" 11"

SPECIFICATIONS			
Bottom Flange	7-1/16" 2/3M DD	7-1/16" 3M	11" 3M
Bottom Connection	API 6A	API 6A	API 6A
Working Pressure	2000 PSI	3000 PSI	3000 PSI
Test Pressure	4000 PSI	6000 PSI	6000 PSI
Max. Slip Load (2:1 SF)	85,000 PSI	85,000 PSI	85,000 PSI
Cap Thread	8-5/8" API Modified	8-5/8" API Modified	8-5/8" API Modified
Cap Material	Ductile Iron	Ductile Iron	Ductile Iron
Inner String & * Stripper Rubber	2-1/16", 2-3/8", 2-7/8", 3-1/2", 4" & 4-1/2"	2-1/16", 2-3/8", 2-7/8", 3-1/2", 4" & 4-1/2"	2-1/16", 2-3/8", 2-7/8", 3-1/2", 4" & 4-1/2"
Suspension	Slips or Mandrel	Slips or Mandrel	Slips or Mandrel
Side Outlet	2" LP	2" LP	2" LP
Minimum Bore	6.551"	6.551"	6.551"
Body Material	Carbon Steel	Carbon Steel	Carbon Steel
Height	19"	19"	19"
Weight	220 lbs	230 lbs.	340 lbs.

* Stripper Rubber only available through 3-1/2"