



MODEL "92"

SPECIFICATIONS				
Bottom Thread	7" O.D. 8rd*	7-5/8" O.D. 8rd*	8-5/8" O.D. 8rd*	9-5/8" O.D. 8rd*
Bottom Connection	Male, Female, SOW	Male, Female, SOW	Male, Female, SOW	Male, Female, SOW
Working Pressure	2000 & 3000 PSI	2000 & 3000 PSI	2000 & 3000 PSI	2000 & 3000 PSI
Test Pressure	4000 & 6000 PSI	4000 & 6000 PSI	4000 & 6000 PSI	4000 & 6000 PSI
Max. Slip Load (2:1 SF)	176,000 lbs.	176,000 lbs.	176,000 lbs.	160,000 lbs.
Cap Thread	8-5/8" API Mod.**	9-5/8" API Mod.**	10-3/4" API Mod.**	11-3/4" API Mod.**
Cap Material	Ductile Iron	Ductile Iron	Ductile Iron	Ductile Iron
Inner String	2-3/8", 2-7/8", 3-1/2", 4-1/2", 5-1/2"	2-3/8", 2-7/8", 3-1/2", 4-1/2", 5-1/2"	2-3/8" thru 3-1/2", 4-1/2", 5-1/2", 7"	2-3/8" thru 3-1/2", 4-1/2", 5-1/2", 7"
Suspension	Slip or Mandrel	Slip or Mandrel	Slip or Mandrel	Slip or Mandrel
Side Outlet	2" LP	2" LP	2" LP	2" LP
Minimum Bore	6.551"	6.937"	8.000"	8.875"
Body Material	Carbon Steel	Carbon Steel	Carbon Steel	Carbon Steel
Height	14"	14"	14"	14"
Weight	90 lbs.	125 lbs.	137 lbs.	150 lbs.

* Other thread styles available upon request of special order

** Caution: WSI recommends using only API modified threaded WSI drilling flanges



**MODEL "92" CASING HEAD
C-22 PROFILE**

SPECIFICATIONS

Bottom Thread	10-3/4" O.D. 8rd*	11-3/4" O.D. 8rd*	12-3/4" O.D. 8rd*	13-3/8" O.D. 8rd*
Bottom Connection	Male, Female, SOW	SOW	SOW	SOW
Working Pressure	2000 PSI	2000 PSI	2000 PSI	2000 PSI
Test Pressure	4000 PSI	4000 PSI	4000 PSI	4000 PSI
C-22 Hanger Load	200,000 lbs.	200,000 lbs.	200,000 lbs.	200,000 lbs.
Cap Thread	12-3/4" 8V LP**	16" O.D. 8RD**	16" O.D. 8RD**	16" O.D. 8RD**
Cap Material	Ductile Iron	Ductile Iron	Ductile Iron	Ductile Iron
Inner String	4-1/2", 5-1/2", 7"	4-1/2", 5-1/2", 7", 7-5/8"	4-1/2", 5-1/2", 7", 7-5/8", 8-5/8"	4-1/2", 5-1/2", 7", 7-5/8", 8-5/8", 9-5/8"
Suspension	Slip or Mandrel	Slip or Mandrel	Slip or Mandrel	Slip or Mandrel
Side Outlet	2" LP	2" LP	2" LP	2" LP
Minimum Bore	9.922"	10.875"	12.000"	12.969"
Body Material	Carbon Steel	Carbon Steel	Carbon Steel	Carbon Steel
Height	16"	19"	19"	19"
Weight	175 lbs.	450 lbs.	440 lbs.	430 lbs.

* Other thread styles available upon request of special order

** Caution: WSI recommends using only WSI drilling flanges