



SPECIFICATIONS			
Bottom Thread	4-1/2" O.D. 8rd	5-1/2" O.D. 8rd	7" O.D.8rd
Bottom Connection	Male, Female	Male, Female	Male, Female
Working Pressure	2000 PSI	2000 PSI	2000 PSI
Test Pressure	4000 PSI	4000 PSI	4000 PSI
Max. Slip Load (2:1 SF)	85,000 lbs.	85,000 lbs.	85,000 lbs.
Cap Thread	8-5/8" Full API	8-5/8" Full API	8-5/8" Full API
Cap Material	Carbon Steel	Carbon Steel	Carbon Steel
Inner String & Stripper Rubbers	2-3/8" & 2-7/8"	2-3/8", 2-7/8", 3-1/2" & 4"	2-3/8", 2-7/8", 3-1/2", 4" & 4-1/2"
Suspension	Slip or Mandrel	Slip or Mandrel	Slip or Mandrel
Side Outlet	2" LP	2" LP	2" LP
Minimum Bore	4.000"	5.012"	6.551"
Body Material	Carbon Steel	Carbon Steel	Carbon Steel
Height	12-1/2" (A7S 18-1/2")	12-1/2" (A7S 18-1/2")	12-1/2" (A7S 18-1/2")
Weight	105 lbs. (A7S 160 lbs.)	105 lbs. (A7S 160 lbs.)	105 lbs. (A7S 160 lbs.)