

Series 25 & Series 40 Series Polished Rod Clamps

- Friction Style – Series 40
- Friction Style – Series 25
- Zinc phosphate coating for better corrosion resistance



Series 25

Series 40



Series 10S

Series 10D

Series 10T

Series 10S, 10D & 10T Polished Rod Clamps

- Most economical design in the industry
- Indention style clamps
- High load limits, yet light & easy to handle
- Lower stress concentrations on polished rods
- Independently hinged segments
- Highest clamping capacity at any bolt torque
- Small diameter for use with rod rotators
- Zinc phosphate coating for better corrosion resistance

SPECIFICATIONS	SERIES 25	SERIES 40	SERIES 10S	SERIES 10D	SERIES 10T
Rated Load	25,000 lbs.	40,000 lbs.	13,000 lbs.	26,000 lbs.	40,000 lbs.
Max. Test Load	35,000 lbs.	55,000 lbs.	32,000 lbs.	64,000 lbs.	76,000 lbs.
Polished Rod Size	1-1/8", 1-1/4", 1-5/16", 1-1/2"	1-1/8", 1-1/4", 1-5/16", 1-1/2", 1-3/4"	1", 1-1/8", 1-1/4", 1-5/16", 1-1/2"	1", 1-1/8", 1-1/4", 1-5/16", 1-1/2"	1", 1-1/8", 1-1/4", 1-5/16", 1-1/2"
Recommended Max. Bolt Torque	250 ft.-lbs.	550 ft.-lbs.	250 ft.-lbs.	250 ft.-lbs.	250 ft.-lbs.
Weight	10.5 lbs.	25 lbs.	3.75 lbs.	7.5 lbs.	11.25 lbs.
Height	4-1/8"	6-3/4"	2-1/2"	5"	7-1/2"
Rotating Diameter	9"	9"	5-3/4"	5-3/4"	5-3/4"
Body Material	Forged Steel	Forged Steel	Forged Steel	Forged Steel	Forged Steel

Important Note: All polished rod clamp bolts must be torqued to specifications noted in table using a calibrated torque wrench.