

The stuffing box is perhaps the most important piece to your artificial lift surface hookup from the standpoint, it is your **SEAL**. The most important component to the stuffing box sealing is the packing inside the stuffing box. WSI continually tests new and better materials to meet the demands for ever-changing well conditions. By working with rubber manufacturers and field testing new designs, WSI wants to make certain that our packing stands up to stringent durability and performance standards. Cone packing is available in sizes for all polished rods 1" through 1-3/4" in sets of 4 (3 top cone and 1 bottom cone).

**Soft Cone Packing**

For sweet crudes with high oil-to-water ratios and low abrasives

**Teflon Cone Packing**

For sweet crudes with low oil-to-water ratios and/or for reducing polish rod noise in noise-sensitive areas

**Brass Filled Cone Packing**

For sweet crudes with high oil-to-water ratios and low abrasives. Good for reducing polished rod scale build-up

**Hard Cone Packing**

For sweet crudes with low oil-to-water ratios

**High Temperature Cone Packing**

For steam injection wells producing sweet crude

**HSN Cone Packing**

For H<sub>2</sub>S and CO<sub>2</sub> wells



**Fluid Seal™ Packing**

For 3000 PSI applications and pressure energized seal



**"V" Style Packing**

Available in NBR or HSN compounds. Used in ELUG™ for both "Classic" and "Premium" stuffing box models

**Important Note:** The guidelines on this page are for general purposes only and should not be used as the sole determining factor for packing material selection. Each down hole condition is different and must be addressed on a case-by-case basis to determine the best material solution for your particular well condition.