







Elevator

Type	Rating (ton)	Size (in)		Type	Rating (ton)	Size (in)	
Slip				Center Latch (90°), Continued			
LYT	20	1.050 to 2-1/16		TA	150	4-1/2 to 8-5/8	
MYT	40	1.315 to 2-7/8		RA	125	2-3/8 to 4-1/2	
YT	75	1.315 to 3-1/2		MAA	175	3-1/2 to 5-1/2	
HYT	150	2-3/8 to 3-1/2		RA	250	3-1/2 to 7	
YC	75	3-1/2 to 7		RA	350	4-1/2 to 7	
MYC	125	3-1/2 to 7		Side Door (90°)			
HYC	200	3-1/2 to 7-5/8		SLX	100	4-1/2 to 5-1/2	
Center Latch (18°)				SLX	150	4-1/2 to 36	
MG	100	2-3/8 to 5-1/2		SLX	250	6-5/8 to 36	
RG	150	2-3/8 to 4-1/2		SX	350	6-5/8 to 20	
MGG	175	2-3/8 to 5		SX	500	6-5/8 to 20	
MGG	250	3-1/2 to 5-1/2		Single Joint			
GG	350	3-1/2 to 5-1/2		S	5	2-3/8 to 36	
Center Latch (90°)				Sucker Rod			
TA	35	1.050 to 2-7/8		Plate	20	5/8 to 1-1/4	
TA	65	1.660 to 4-1/2		Solid	20	5/8 to 1-1/2	
TA	100	2-3/8 to 8-5/8					